

# DTEN GO with Mate PoE Including Mate Dock



**DTEN GO**



\*Secure Locking Bezel Frame included

**DTEN Mate PoE + Dock**

Software	DTEN OS
Display	Utilizes connected display
Placement	Mount above or below TV or display
Camera System	Camera array: up to 16.4ft (5m) coverage Horiz. field of view (HFOV): 160° combined
Audio System	12 Microphone array Up to 16.4ft (5m) coverage Acoustic Echo Cancellation Automatic Gain Control (AGC) AI-based Noise Cancellation DTEN Smart Connect
Network	Ethernet (RJ-45) WiFi 2.4Ghz & 5Ghz IPv4 Dynamic Host Configuration Protocol (DHCP)/ Static HTTP/HTTPS Proxy Support
Inputs & Outputs	Ethernet LAN (RJ45) x 1 3.5mm Audio Jack x 1 HDMI Out x 2 USB Type-C x 1
In the Box	Power cord and adapter HDMI cable x 2 Ethernet cable x 1
Power	100 to 240 VAC, 50 to 60 Hz
Product Dimensions	10.7 x 2.1 x 2.75 in (272 x 54 x 69mm)
Product Weight	1.3 lb (0.6kg)
Operating Temperature and Humidity	Operating Temperature 0°C to 40°C Storage Temperature -10°C to 60°C Operating Humidity 20% to 80% RH Storage Humidity 10% to 60% RH

Software	DTEN Mate OS
Display	LED 10.1" Capacitive Multi-touch Display
Placement	Mountable on table, wall or mullion
Network	PoE 802.3af WiFi 2.4Ghz & 5Ghz
Inputs & Outputs	USB Type-C x1 Ethernet x1
In the Box	DTEN Mate DTEN Mate dock Secure locking bezel Wall-mounting kit Door frame (mullion) mount kit Power cord and adapter
Power	100 to 240 VAC, 50 to 60 Hz
Product Dimensions	3.09 x 9.51 x 6.05 (7.9 x 24.2 x 15.4 cm)
Product Weight	Mate 0.495 kg Dock 1.25kg
Power	100 to 240 VAC, 50 to 60 Hz



\*Secure Locking Bezel Frame included